





F2

HP 25 / 50 - KW 18 / 37

ROTARY CULTIVATOR WITH CHAIN TRANSMISSION

F2

HP 25 / 50 - KW 18 / 37



STANDARD EQUIPMENT

- Safety guards CE
- Three-point hitch
- Rotor with four curved blades per disc
- Depth regulating skids
- PTO shaft with shear bolt
- PTO 540 rpm
- Rotor speed 208 rpm

OPTIONS

- Rotors with six blades per disc
- Front wheels in iron
- Spike or Cage roller

ALTERNATIVES

- 90° blades
- Rotor with blades facing inwards

MODELLO	 cm	 cm	 cm	 HP KW	 cm	 .N	 .Kg
F2-180	192	180	90 — 90	35 - 50	17	9	320
F2-170	182	170	85 — 85	35 - 50	17	9	315
F2-165	177	165	85 — 85	35 - 50	17	9	310
F2-160	172	160	80 — 80	35 - 50	17	8	305
F2-150	162	150	75 — 75	35 - 50	17	8	294
F2-145	157	145	75 — 75	35 - 50	17	7	290
F2-140	152	140	70 — 70	35 - 50	17	7	287
F2-130	142	130	65 — 65	25 - 40	17	7	279
F2-120	132	120	60 — 60	25 - 40	17	6	254
F2-100	112	100	50 — 50	25 - 40	17	5	230