

F4LP

HP 40 / 75- KW 37 / 78

**ROTARY CULTIVATOR WITH TRACTOR OPERATED HYDRAULIC SIDE SHIFT AND
THREE-SPEED LEVER OPERATED GEARBOX**

F4LP

HP 40 / 75- KW 37 / 78



STANDARD EQUIPMENT








- Safety guards CE
- Three-point hitch
- Hydraulic side-shift on chromium-plated shaft
- Rotor with four curved blades per disc
- Front depth regulating skids
- Three-speed lever gear change
- PTO shaft with clutch
- Hydraulic piston
- PTO 540 rpm

ALTERNATIVES

- 90° blades
- Rotor with internal facing blades
- Side depth regulating skids

OPTIONS

- PTO shaft (Cuna) with clutch
- Rotor with six blades per disc
- Front wheels in iron

MODELLO	 cm	 cm	 cm	 HP KW	 cm	 .N	 .Kg
F4LP-220	229	220	110_110 72_148	45 - 70	22	9	639
F4LP-210	219	210	105_105 67_143	45 - 75	22	9	595
F4LP-185	184	185	93_92 55_130	45 - 75	22	8	538
F4LP-170	179	170	85_85 47_123	45 - 75	22	7	521
F4LP-160	169	160	80_80 42_118	40 - 75	22	7	497
F4LP-145	154	145	73_72 31_114	40 - 75	22	6	486
F4LP-135	144	135	70_65 27_108	40 - 75	22	6	475