



PH6

HP 160 / 300 - KW 118 / 218

FOLDABLE POWER HARROW WITH THREE-SPEED EXTERNAL LEVER OPERATED GEARBOX

PH6

HP 160 / 300 - KW 118 / 218




	1°	2°	3°	
				g / m rpm U/min tr/min
1000 g/m	310	410	495	

STANDARD EQUIPMENT

- Safety guards
- PTO 1000 rpm
- Three-speed lever gear change
- (Rotor speed: 1° 310 rpm, 2° 410 rpm, 3° 495 rpm)
- Floating or fixed working position
- Three-point hitch (Category 2 and 3) with oscillating arms
- Rear roller (Packer Ø 513mm exterior, Ø 355 mm tube)
- Rear light bar
- Soil refinement bar
- Predisposition for rear seed-drill
- Side PTO shaft with bolt limiter
- Central PTO shaft
- Protection from stones, removable

OPTIONS

- PTO shaft with clutch
- Pair of track eradicators
- Central PTO shaft, serie 12
- 35 cm tines
- Packer roller Ø 615 mm exterior, Ø 457 mm tube
- Rear rollers with hydraulic regulation
- PTO shaft with pawl limiter
- Oil-cooling kit

MODELLO	 cm	 cm	 cm	 HP KW	 cm	 .N	 .Kg	 Kg	 Kg
PH6-600	615	600	300__300	160-300 118-218	28	24	48	3410	3680
PH6-500	515	500	250__250	160-300 118-218	28	20	40	3057	3305
PH6-400	415	400	200__200	160-300	28	32	32	2710	2921