




T10S

HP 35 - 95 / KW 28 - 70

PRUNING AND GRASS FLAIL MOWER WITH TRACTOR OPERATED HYDRAULIC SIDE SHIFT

T10S

HP 35 - 95 / KW 28 - 70



STANDARD EQUIPMENT








- Safety guards CE
- PTO shaft
- Oil quenced free-wheel in gearbox
- Wear-resistant inner lining
- Adjustable rear roller with roller cleaner
- Rotor with heavy flat hammers with pin ø 22
- Wood-gathering spikes
- Machine support
- Double row of front protection plates
- PTO 540 rpm

OPTIONS

- Front wheels in iron
- Steerable iron wheels
- Steerable rubber wheels
- Pair of skids
- Wear-resistant inner lining in HARDOX
- PTO 1000 rpm

ALTERNATIVES

- Blades
- Toothed hammers

| MODELLO |  cm |  cm |  cm |  HP KW |  .N |  .N |  .Kg |
|----------|--|--|--|---|--|--|---|
| T10S-285 | 310 | 285 | 142__143 | 70 - 95 | 32 | 64 | 855 |
| T10S-250 | 275 | 250 | 125__125 | 70 - 90 | 22 | 66 | 765 |
| T10S-220 | 245 | 220 | 110__110 | 70 - 85 | 20 | 60 | 699 |
| T10S-200 | 219 | 200 | 101__101 | 50 - 75 | 18 | 54 | 648 |
| T10S-180 | 199 | 180 | 90__90 | 50 - 75 | 16 | 48 | 618 |
| T10S-160 | 178 | 160 | 80__80 | 40 - 70 | 14 | 42 | 578 |
| T10S-150 | 167 | 150 | 75__75 | 40 - 70 | 14 | 42 | 550 |
| T10S-140 | 158 | 140 | 70__70 | 35 - 70 | 12 | 36 | 502 |
| T10S-130 | 148 | 130 | 65__65 | 35 - 70 | 12 | 36 | 465 |