

T15

HP 60 / 250- KW 52 / 210

STRAW AND STUBBLE SHREDDER

T15

HP 60 / 250- KW 52 / 210










STANDARD EQUIPMENT

- Safety guards CE
- PTO shaft
- Oil quenched free-wheel in gearbox
- Oversized rotor with blades
- Opening shutter only for maintenance purposes
- Straw spreader
- PTO 540 rpm
- PTO 1000 rpm
- Rear leveling roller or rubber steering wheels
- Double row of front protection flags

OPTIONS

- Hydraulic side shift on chromium-plated shaft
- Pair of wheels, also in reverse
- Counter blades
- Pair of skids
- Pair of wide skids
- Front chain, instead of flags
- Gearbox B&P 2071
- Side transmission with drive-shaft
- Rotor with large flat hammer
- Pair of steering wheels, also in reverse

MODELLO	 cm cm	 cm	 cm	 HP	 .N	 .N	 .Kg
T15-460 DT2R	512	460	230_230	150-250	-	104	2340
T15-400 DT2R	446	400	200_200	140-250	-	96	2040
T15-360 DT 1R	406	360	180_180	110-200	-	84	1720
T15-320 DT 1R	347	320	160_160	110-200	-	80	1376
T15-320	347	320	160_160	90-180	-	80	1340
T15-300	327	300	150_150	90-180	-	72	1284
T15-280	307	280	140_140	90-180	-	68	1160
T15-250	277	250	125_125	70-180	24	56	1095
T15-230	257	230	115_115	70-180	22	52	984
T15-200	230	205	102_102	70-180	18	48	850
T15-180	205	180	90_90	70-105	16	40	823

ALTERNATIVE

- Right angle knives