





T9

HP 35 / 70 - KW 26 / 52

PRUNING AND GRASS FLAIL MOWER

T9

HP 35 / 70 - KW 26 / 52



STANDARD EQUIPMENT







- Safety guards CE
- PTO shaft
- Oil quenced free-wheel in gearbox
- Flat hammers
- Detachable counter plate cutters
- Wood gathering spikes
- Machine support
- Adjustable rear roller
- Double row of protection plates
- Movable hitches
- Opening shutter only for maintenance purposes
- PTO 540 rpm

OPTIONS

- Anti-wearing plate
- Rotor with heavy hammers with pin Ø 22 (flat or toothed)
- Fixed or steerable iron wheels
- Fixed or steerable rubber wheels
- Pair of skids
- Rotor with flat hammers, serie "X"

ALTERNATIVE

- Blades

MODELLO	 cm	 cm	 cm	 HP KW	 .N	 .N	 .Kg
T9-250	264	250	125__125	50 - 70	26	52	752
T9-220	234	220	110__110	50 - 70	24	48	672
T9-200	214	200	100__100	50 - 70	22	44	548
T9-180	194	180	90__90	40 - 70	20	40	520
T9-160	173	160	80__80	40 - 70	18	36	473
T9-150	163	150	75__75	40 - 70	16	32	413
T9-140	153	140	70__70	35 - 70	16	32	401
T9-130	143	130	65__65	35 - 70	14	28	385