





**T9S**

HP 35 / 70 - KW 26 / 52

PRUNING AND GRASS FLAIL MOWER WITH TRACTOR OPERATED HYDRAULIC SIDE SHIFT

# T9S

HP 35 / 70 - KW 26 / 52



## STANDARD EQUIPMENT








- Safety guards CE
- Hydraulic side shift on chromium-plated shaft
- PTO shaft
- Oil quenched free-wheel in gearbox
- Flat hammers
- Detachable counter plate cutters
- Wood-gathering spikes
- Machine support
- Adjustable rear roller
- PTO 540 rpm
- Opening shutter only for maintenance purposes
- Double row of front protection plates

## OPTIONS

- Anti-wearing plate
- Rotor with heavy hammers with pin Ø 22 (flat or toothed)
- Steerable iron wheels
- Steerable rubber wheels
- Pair of skids
- Rotor with flat hammers, serie "X"

## ALTERNATIVE

- Blades

MODELLO	 cm	 cm	 cm	 HP KW	 .N	 .N	 .Kg
T9S-250	264	250	125__125	50 - 70	26	52	850
T9S-220	234	220	110__110	50 - 70	24	48	775
T9S-200	214	200	100__100	50 - 70	22	44	635
T9S-180	194	180	90__90	40 - 70	20	40	601
T9S-160	173	160	80__80	40 - 70	18	36	548
T9S-150	163	150	75__75	40 - 70	16	32	483
T9S-140	153	140	70__70	35 - 70	16	32	472
T9S-130	143	130	65__65	35 - 70	14	28	460