



V25
HP 30 / 75 - KW 22 / 56

HEAVY DUTY SPADER WITH THREE-SPEED LEVER OPERATED GEARBOX

V25

HP 30 / 75 - KW 22 / 56




STANDARD EQUIPMENT

- Safety guards CE
- Three-point hitch
- Rake
- Internal / external depth regulating skids
- Three-speed lever gear change
- PTO shaft with clutch
- PTO 540 rpm
- External frame supports

OPTIONS

- Tailgate
- Depth regulating wheels for models 175 - 200
- Supports with bushings
- Hydraulic side-shift – 20 cm left, 20 cm right
- Hydraulic side-shift – 40 cm right only
- Support with double-row ball bearings

MODELLO	 cm	 cm	 cm	 HP KW	 cm	 .N	 .Kg
V25-200	209	200	100 — 100	50 - 75	30	8	891
V25-190	195	190	95 — 95	50 - 75	30	8	830
V25-175	180	175	87 — 88	35 - 75	30	8	769
V25-165	173	165	82 — 83	35 - 70	30	6	641
V25-155	162	155	77 — 78	35 - 70	30	6	630
V25-145	152	145	72 — 73	35 - 70	30	6	612
V25-135	144	137	68 — 69	35 - 70	30	6	592
V25-120	129	120	60 — 60	35 - 70	30	6	580
V25-100	109	100	50 — 50	35 - 70	30	4	495