










V43

HP 90 / 195 - KW 66 / 143

DEEP SPADER WITH THREE-SPEED LEVER OPERATED GEARBOX

V43

HP 90 / 195 - KW 66 / 143

MODELLO	 cm	 cm	 cm	 HP KW	 cm	 .N	 .Kg
V43-400	430	400	200 _ 200	135 - 195	38	14	2650
V43-350	373	350	175 _ 175	130 - 195	38	12	2387
V43-300	316	300	150 _ 150	100 - 180	38	10	2107
V43-250	259	250	125 _ 125	90 - 180	38	8	1750
V43-185	190	185	92 _ 93	90 - 110	38	6	1447

STANDARD EQUIPMENT

- Safety guards CE
- Three-point hitch
- Leveling rake with regulating jack
- Three-speed lever gear change
- Side guards
- PTO shaft with clutch for models 185 - 300
- PTO shaft with pawl limiter for models 350 and 400
- PTO 1000 rpm
- Depth regulating wheels
- Rear PTO for models 250 - 400
- External frame supports
- Oil cooling kit for models 350 and 400
- Manual jack for wheel depth regulation

OPTIONS

- Rear PTO
- Rear hydraulic three-point hitch
- Oil cooling kit (necessary for tractors above 160 HP)
- PTO shaft pawl limiter (necessary for tractors above 160 HP)
- Hydraulic jacks for rake adjustment
- Transport trolley kit
- Rotating, depth regulating skids
- Hydraulic jacks for wheel depth regulation
- Extension kit for three-point hitch

ALTERNATIVE

- PTO 540 rpm (only for model 185)